



# ENERGY

# 8.1LT

56100022
Rev: 1
Units
Std Metric

8.1L CAC			
1500		1800	

General Engine Data						
Type	N/A		In-Line 4 cycle			
Number of cylinders	N/A		6			
Aspiration	N/A		Turbo Charge Air Cooled			
Bore	in	mm	4.37	111	4.37	111
Stroke	in	mm	5.47	139	5.47	139
Displacement	in^3	L	492	8.1	492	8.1
Compression Ratio	N/A		10.5			
Mean Piston Speed	ft/min	m/s	1368	6.95	1641	8.34
Gross Standby Power Rating <sup>1,2,3</sup> Per ISO 3046 at the Flywheel						
NG	Hp	kW	194	145	236	176
LP	Hp	kW	137	102	174	130
MEP (@ rated Load on NG)	psi	bar	209	14	211	15
MEP (@ rated Load on LP)	psi	bar	147	10	156	11
Gross Prime Power Rating <sup>1,2,3</sup> Per ISO 3046 at the Flywheel						
NG	Hp	kW	175	131	201	150
LP	Hp	kW	123	92	148	111
MEP (@ rated Load on NG)	psi	bar	188	13	179	12
MEP (@ rated Load on LP)	psi	bar	132	9.1	132	9.1
RPM Range (Min-Max)	RPM		1500-2000			
Rotation Viewed from Flywheel	N/A		Counter Clockwise			
Firing Order	N/A		1-5-3-6-2-4			
Dry Weight						
Fan to Flywheel	lb	kg	2200	998	2200	998
Rad to Flywheel	lb	kg	2660	1207	2660	1207
Wet Weight						
Fan to Flywheel	lb	kg	2288	1042	2288	1022
Rad to Flywheel	lb	kg	2860	1311	2860	1292
CG						
Distance from FW housing	in	mm	17	426	17	426
Distance above center of crankshaft	in	mm	7	184	7	184
Engine Mounting						
Maximum Allowable Bending Moment at Rear of Block	lb ft	N m	6638	9000	6638	9000
Moment of Inertia About Roll Axis	lb ft^2	kg m^2				
Flywheel housing	N/A		SAE No 2			
Flywheel	N/A		No 11 1/2			
Number of Flywheel Teeth	N/A		140			
Exhaust System						
Type			Water Cooled Manifold			
Maximum allowable Back pressure	in HG	kPa	3	10.2	3	10.2
Standard Catalyst Back pressure	in HG	kPa	1.5	5.1	1.5	5.1
Exhaust Outlet Pipe Size						
Maximum Turbine Inlet Temperature	F	C	1382	750	1382	750
Exhaust Flow at Rated Power	lb/hr	kg/hr	1241	563	1481	672
Exhaust Flow at Rated Power @1350F	cfm	m^3/min	946	26.8	1129	31.9
Air Induction System						
Maximum allowable Intake Air Restriction with Air Cleaner						
Clean	inH2O	kPa	5	1.24	5	1.24
Dirty	inH2O	kPa	15	3.74	15	3.74
Combustion Air required (entire engine)	lb/hr	kg/hr	1171	531	1397	634
Combustion Air required (entire engine)	cfm	m^3/min	297	8	355	10



# ENERGY

# 8.1LT

56100022
Rev: 1
Units
Std Metric

8.1L CAC			
1500		1800	

Electrical System							
Minimum Recommended Battery Capacity	AH		150				
Cold Cranking Current							
Engine only	CCA		900				
Engine with Drive train	CCA		900				
Maximum Allowable Resistance of Starting Circuit	Ohms		0.002				
Starting Motor Power	HP	kW	6.0	4.5	6.0	4.5	
Battery Charging Alternator							
Voltage	Volts		24				
Current	Amps		45				
Coil primary Resistance	Ohms		0.59Ω ± 10%				
Spark Plug p/n			IFR7F-4D				
Spark plug gap	inches	mm	.015" (-0/+ .008") .38mm (-0/+ .2mm)				
Cooling System							
Coolant Capacity							
Engine only	gal	L	5	22.7	5	22.7	
Engine with Radiator	gal	L	17.5	80	17.5	80	
Engine Coolant Flow	gal/min	L/min	53	200	63	240	
Water Pump Speed	RPM		1950		2340		
Heat rejected to Cooling water at rated Load	btu/min	kcal/sec	7690	32.3	9357	39.3	
Maximum Intake Air Temperature (IAT)	F	C	155	68	155	68	
ECU IAT Warning	F	C	140	60	140	60	
ECU IAT Shutdown	F	C	155	69	155	69	
Maximum Coolant Friction Head External to the engine	psi	bar	5.8	0.4	5.8	0.4	
Maximum Air Restriction Across a Radiator	inH2O	mmH2O	0.5	12.8	0.5	12.8	
Standard Thermostat Range							
Cracking Temperature	F	C	160	71	160	71	
Full Open Temperature	F	C	185	85	185	85	
Maximum Output Pressure of Engine Water Pump							
Maximum Allowable Pressure Cap	psi	bar	14.7	1	14.7	1	
Ambient Clearance Open Genset (water) (Air-to-Boil)							
Specified	F	C	142	61	142	61	
Actual	F	C			149	65	
Ambient Clearance (Oil)							
Specified	F	C	142	61	142	61	
Actual	F	C			145	63	
CAC Rise over Ambient (Charge)							
Specified	F	C	15	9	15	9	
Actual	F	C			14	8	
Maximum Allowable Top Tank Temperature	F	C	230	110	230	110	
ECU Warning	F	C	220	104	220	104	
ECU Shutdown	F	C	230	110	230	110	
Fan Power	HP	kW	4.5	3.4	8.0	7.5	
Fan Diameter, including blades	in	mm	28	711	28	711	
Fan Speed	RPM		1950		2340		
Cooling Fan Air Flow @ 1" Static H2O Pressure and 125F @ radiator	CFM	m³/min	10,714	303	12,500	354	
Charge Air Cooler							
Compressor Outlet Temperature	F	C	225	107	230	110	
Compressor Flow Rate per CAC	lb/hr	kg/hr	1241	563	1481	672	
Heat Rejection per CAC	btu/min	kW	TBD		760	13.4	



# ENERGY

# 8.1LT

56100022
Rev: 1
Units
Std Metric

8.1L CAC			
1500		1800	

Lubrication System			
Oil Specification	SAE 15W-40 Low Ash Gas engine oil (.25-.5% by wt), API CD/CF or higher		
Oil Pressure			
Idle			
Min	Psi	Bar	11 0.8 11 0.8
Max	Psi	Bar	20.3 1.4 20.3 1.4
Rated Speed			
Min	Psi	Bar	20.3 1.4 20.3 1.4
Max	Psi	Bar	70 4.8 70 4.8
Maximum Allowable Oil Temperature	F	C	250 121 250 121
Engine Oil Capacity			
Min	Qts	L	18 17 18 17
Max	Qts	L	25 24 25 24
Oil Filter Capacity	Qts	L	3.75 3.5 3.75 3.5
ECU Oil Pressure Warning <sup>5</sup>	psi		30
ECU Oil Pressure Shut Down <sup>5</sup>	psi		25
Fuel System			
Fuel Consumption <sup>6</sup>			
NG	Ft <sup>3</sup> /hr	kg/hr	1451 29 1775 36
LP	Ft <sup>3</sup> /hr	kg/hr	420 22 544 29
Maximum EPR Rated Pressure	psi	kPa	1.0 6.9 1.0 6.9
Maximum Running pressure to Electronic Pressure Regulator (EPR)	inH2O	kPa	11.0 2.7 11.0 2.7
Minimum Running pressure to EPR	inH2O	kPa	7.0 1.7 7.0 1.7
Minimum Gas Supply Pipe Size	1-1/4" NPT		
Maximum EPR Rated Pressure	psi	kPa	1.0 6.9 1.0 6.9
Maximum Running Pressure to EPR	inH2O	kPa	11.0 2.7 11.0 2.7
Minimum Running Pressure to EPR	inH2O	kPa	7.0 1.7 7.0 1.7
Minimum LPG Supply Pipe Size <sup>4</sup>	1-1/4" NPT		

<sup>1</sup>Standby and overload ratings based on ISO3046.

<sup>2</sup> All ratings are gross flywheel horsepower corrected to 77°F at an altitude of 328feet with no cooling fan or alternator losses using heating value for NG of 1015 BTU/SCF.

<sup>3</sup> Production tolerances in engines and installed components can account for power variations of +/- 5%. Altitude, temperature and excessive exhaust and intake restrictions should be applied to power calculations.

<sup>4</sup> The preceeding pipe sizes are only suggestions and piping sizes may vary with temperature, pressure, distance from supply and application of local codes. Gas must be available at adequate volume and pressure for engine at the EPR.

<sup>5</sup> >1400RPM

<sup>6</sup> See PSI Energy Technical Spec. 56100019 - Fuel Specification. Gas properties for fuel consumption data: NG: Density =0.717 kg/m3, LHV = 927 BTU/scf; Propane: Density = 1.882 kg/m3, LHV = 2316 BTU/scf