	Model : <b>12M55G8D0/5</b>	Date : 22/03/23
	<b>PowerKit Engine Datasheet - DCP</b>	Page : 1 / 4

## Ratings

RPM	Gross Engine Output				Net Engine Output *			
	Data Centre Power (DCP)		ESP		Data Centre Power (DCP)		ESP	
	kWm	BHP	kWm	BHP	kWm	BHP	kWm	BHP
1500	2420 *	3245 *	2700	3621	2302 *	3088 *	2582	3463


1 kWm = 1,34102 BHP

\* When the engine is used with a cooling system using an electrically driven fan, net engine output data may change and quoted figures should be used for reference only

## Basic data

Engine model	12M55G8D0/5
N° of Cylinders / Valves	12 / 48
Cylinders arrangement	At Vee
Bore x Stroke (mm)	180 x 215
Displacement (L)	65.65
Thermodynamic Cycle	Diesel 4 stroke
Firing Order	A1-B1-A5-B5-A3-B3-A6-B6-A2-B2-A4-B4
Mean Piston Speed (m/s)	10.75
BMEP (Bar)	32.9
Cooling System	Liquid (water + 50% antifreeze)
Injection System	Direct
Fuel System	High Pressure Common Rail
Aspiration	Turbocharged and Aftercooled
Compression ratio	16.5 : 1
Flywheel housing	SAE 00
Flywheel	21"
Rotation Viewed from Flywheel	Counter Clockwise
Allowed static bending moment of the flywheel housing	TBD
N° of teeth on flywheel ring gear	202
Inertia of flywheel (kg•m²)	20.78
Inertia of crankshaft (kg•m²)	16.16
Emission standard	N/A
Overall Dimensions with radiator (Length x Width x Height) (mm)	4193 x 2241 x 2787
Engine dry weight without radiator and without radiator pipes (kg)	9550
Engine dry weight with radiator and radiator pipes (kg)	11500
Engine wet weight with radiator (includes oil, coolant) (kg)	12486

DPK-TDS-EN-12M55-0035-23-03-22 Moteurs Baudouin reserve the right to modify these specifications, without notice. Document not contractual.

	Model : <b>12M55G8D0/5</b>	Date : 22/03/23
	<b>PowerKit Engine Datasheet - DCP</b>	Page : 2 / 4

## Air intake system

Air intake temperature rise (°C) .....	≤ 5
Air intake restriction clean filter (mBar) .....	≤ 30
Air intake restriction dirty filter (mBar) .....	≤ 70
Recommended air flow @ DCP (m³/min) .....	157.1
Min. diameter of intake pipe (mm) .....	250

## Aftercooling system

Aftercooler system type .....	Air to Water
Max. intake temperature @ 25°C ambient temperature (°C) .....	55
Max. difference between intake temperature and ambient temperature (°C) .....	TBD
Max. intake pressure drop of aftercooler (mBar) .....	50

## Lubrication system


Oil capacity Low / High (L) .....	330 / 380
Oil pressure in normal condition idle speed (Bar) .....	≥ 1.8
Oil pressure in normal condition at 1500 Rpm @ DCP (Bar) .....	4 - 6.5
Lowest oil pressure alarm (shutdown) (Bar) .....	1.8
High Oil Pressure Warning .....	6.5
Max. oil temperature (°C) .....	105
Oil flow at 1500 Rpm (L/min) .....	1080
Oil fuel consumption ratio based on engine fuel consumption data .....	≤ 0.4g/kW·h
Total system capacity (including filters) (L) .....	460

## Heat balance test data (with ambient temperature 24.4 °C)

Total heat dissipation @ DCP (kJ/s) .....	4131.9
- Heat Rejection to Jacket Water @ DCP (kJ/s) .....	1083.2
- Heat Rejection to LT circuit @ DCP (kJ/s) .....	719
- Radiated Heat to Ambient @ DCP (kJ/s) .....	319.3
- Heat Rejected to Exhaust @ DCP (kJ/s) .....	2010.4

## Exhaust system

Max. exhaust back pressure (mBar) .....	150
Max. exhaust temperature before turbocharger (°C) .....	740
Max. exhaust temperature after turbocharger (°C) .....	TBD
Exhaust flow @ DCP (m³/min) .....	534.2
Min. diameter of exhaust pipe (mm) .....	280
Max. bending moment of exhaust gas exit flange (Nm) .....	10

	Model : <b>12M55G8D0/5</b>	Date : 22/03/23
	<b>PowerKit Engine Datasheet - DCP</b>	Page : 3 / 4

## Cooling system with Made in EU radiator

System designed for ambient temperature up to (°C) <sup>1</sup>	40
Radiator type	Electrical
Fan type	Electric driven pusher - 4 x 30 kWe 400 Vac 1450 Rpm motors
Min. inside diameter of coolant outlet pipe (mm)	96
Coolant capacity of radiator and pipes (L)	220
Coolant alarm (shutdown) temperature (°C)	112
Thermostat opening temperature / full open temperature (°C)	78 / 90
Max. additional restriction for external cooling circuit (Bar)	TBD
Coolant capacity of the engine (L)	306
Cooling fan airflow (m³/min)*	2400
Fan absorbed power (kW)	116
Additional restriction (for reference) - Duct allowance (Pa)	150

\* Air flow figure assumes the presence of the standard radiator provided, taking into consideration the backpressure caused

## Fuel system

Governor	ECU
Governor steady state speed stability at constant load (ISO 8528-5 Class G3) <sup>2</sup>	≤ +/- 0.5 %
Max. restriction at fuel inlet (Bar)	0.1
Max. pressure at fuel inlet (Bar)	0.5
Max. fuel return restriction (Bar)	0.2
Max. fuel inlet temperature (°C)	50
Fuel supply flow (L/hr)	2800
Min. internal diameter of inlet pipe (mm)	19
Min. internal diameter of return pipe (mm)	19


## Electrical system

Electrical system voltage (negative to ground) (Vdc)	24
Starter power (kW)	2 x 8.5
Battery charger current (A)	55
Battery charger absorbed power (kW)	1.6
Max. electric resistance of starting circuit (Ω)	0.008
Min. sectional area of wire (mm²)	2 x 95
Min. cold start temperature without auxiliary starting device (°C) <sup>3</sup>	-10
Min. cold start temperature with auxiliary starting device (°C) <sup>3</sup>	TBD

<sup>1</sup> The indicated value is based on the AOT value of 40°C for an engine tested at 100% of the DCP Power, reflecting temperature in an open condition, without an enclosure or container, without any airflow obstruction in the front of the radiator, without air recirculation, with free exhaust gas exit and with the engine thermostatic valve in its full open condition, without a closing plate present. The reference air restriction is equal to 50Pa. For the equivalent ATB (Air-to-Boil) performance in a customer or project basis, please consult Baudouin Application Engineering.

<sup>2</sup> This refers only to the frequency response of the engine and should not be confused with the performance class of the Generator Set, which is subject to additional contributing factors such as alternator selection and control settings.

<sup>3</sup> Engines used in emergency standby application or applications that require immediate start under load, they must be equipped with coolant heaters. Baudouin recommend heaters installation to be executed by providing constant coolant circulation across all the engine components. Two heaters are required for V-type engines, one per each side.

	Model : <b>12M55G8D0/5</b>	Date : 22/03/23
	<b>PowerKit Engine Datasheet - DCP</b>	Page : 4 / 4

## Noise

Diesel engine noise (Acoustic power level) (dB(A)) .....	124.9
Noise - upper side (dB(A)) .....	106.5
Noise - right side (view from flywheel) (dB(A)) .....	107.1
Noise - left side (view from flywheel) (dB(A)) .....	107.9
Noise – front (radiator) side (dB(A)) .....	107.0
Noise – rear (flywheel) side (dB(A)) .....	106.5

Notes :

- Noise test made at 100% of the power, at 1 mt. distance, on engine without radiator, without cooling fan and without silencer.
- Noise test refers to ISO 6798 norm : "Reciprocating internal combustion engines. Measurement of emitted airborne noise. Engineering method and survey method".

## Fuel consumption

Rating	gr/kWh	L/hr
100% DCP	196.8	567
75% DCP	192.6	416.2
50% DCP	197.2	284.1
25% DCP	217.8	156.9
Fuel consumption tolerance +/- 5%		

## Ratings definitions

### Emergency Standby Power (ESP)

Emergency Standby Power is the maximum power available for a varying load for the duration of a main power network failure. The average load factor over 24 hours of operation should not exceed 70% of the engine's ESP power rating. Typical operational hours of the engine is 200 hours per year, with a maximum usage of 500 hours per year. This includes an annual maximum of 25 hours per year at the ESP power rating. No overload capability is allowed. The engine is not to be used for sustained utility paralleling applications.

### Data Centre Power (DCP)

Data Centre Power is defined as being the maximum power which a generating set is capable of delivering while supplying a variable or continuous electrical load and during unlimited run hours. Depending on the sites to supply and the availability of reliable utility, the generating set manufacturer is responsible to define what power level he is able to supply to fulfil that requirement including hardware or software or maintenance plan adaptation.

Note : The engine driven alternating current generating set is a reliable source of power for the data centre and it can be also used to back up a reliable utility. Prolonged operation at load in parallel with a utility is not permitted.

### Uptime Compliant

This engine rating is compliant with Uptime certified installations

- All ratings are based on operating conditions under ISO 8528-1:2018, ISO 3046, DIN6271. Performance tolerance of  $\pm 5\%$ .
- Test conditions : 100 kPa, 25°C air inlet temperature, relative humidity of 30%, with fuel density 0.84 kg/L. Derating may be required for conditions outside these; please contact the factory for details.
- Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan and optional equipment.