	Model : <b>6M33G6D0/S</b>	Date : 22/03/23
	<b>PowerKit Switchable Engine Datasheet</b>	Page : 1 / 4

## Ratings

RPM	Gross Engine Output				Net Engine Output *			
	PRP kWm	PRP BHP	ESP kWm	ESP BHP	PRP kWm	PRP BHP	ESP kWm	ESP BHP
1500	675	905	725	972	650	872	700	939
1800	670	899	740	992	642	860	712	954


1 kWm = 1,34102 BHP

\* When the engine is used with a cooling system using an electrically driven fan, net engine output data may change and quoted figures should be used for reference only

## Basic data

Engine model	6M33G6D0/S
N° of Cylinders / Valves	6/24
Cylinders arrangement	In line
Bore x Stroke (mm)	150x185
Displacement (L)	9.25
Thermodynamic Cycle	Diesel 4 stroke
Firing Order	
Mean Piston Speed (m/s) - Rpm 1500 / 1800	9.25 / 11.1
BMEP (Bar) - Rpm 1500 / 1800	29.59 / 25.17
Cooling System	Liquid (water + 50% antifreeze)
Injection System	Direct
Fuel System	High Pressure Common Rail
Aspiration	Turbocharged and Aftercooled
Compression ratio	15:1
Flywheel housing	SAE 1
Flywheel	14"
Rotation Viewed from Flywheel	
Allowed static bending moment of the flywheel housing	
N° of teeth on flywheel ring gear	178
Inertia of flywheel (kg•m <sup>2</sup> )	4.76
Inertia of crankshaft (kg•m <sup>2</sup> )	2.22
Emission standard	N/A
Overall Dimensions with radiator (Length x Width x Height) (mm)	2798x1680x1954
Engine dry weight without radiator and without radiator pipes (kg)	2110
Engine dry weight with radiator and radiator pipes (kg)	2472
Engine wet weight with radiator (includes oil, coolant) (kg)	2689

DPK-TDS-EN-6M33-1002-23-03-22 Moteurs Baudouin reserve the right to modify these specifications, without notice. Document not contractual.

	Model : <b>6M33G6D0/S</b>	Date : 22/03/23
	<b>PowerKit Switchable Engine Datasheet</b>	Page : 2 / 4

## Air intake system

Air intake temperature rise (°C) .....	≤ 5
Air intake restriction clean filter (mBar) .....	≤ 30
Air intake restriction dirty filter (mBar) .....	≤ 65
Recommended air flow @ PRP (m³/min) - Rpm 1500 / 1800 .....	43.8 / 53
Recommended air flow @ ESP (m³/min) - Rpm 1500 / 1800 .....	51.5 / 57.3
Min. diameter of intake pipe (mm) .....	140

## Aftercooling system

Aftercooler system type .....	Air to Air
Max. intake temperature @ 25°C ambient temperature (°C) .....	55
Max. difference between intake temperature and ambient temperature (°C) .....	30
Max. intake pressure drop of aftercooler (mBar) .....	150

## Lubrication system


Oil capacity Low / High (L) .....	36/61
Oil pressure in normal condition idle speed (Bar) .....	≥ 2
Oil pressure in normal condition @ PRP (Bar) .....	4 - 6.5
Lowest oil pressure alarm (shutdown) (Bar) .....	2
High Oil Pressure Warning .....	
Max. oil temperature (°C) .....	105
Oil flow (L/min) - Rpm 1500 / 1800 .....	≥263 / ≥316
Oil fuel consumption ratio based on engine fuel consumption data .....	≤ 0.3 %
Total system capacity (including filters) (L) .....	64

## Heat balance test data (with ambient temperature 17.2 °C)

Total heat dissipation @ ESP - Rpm 1500/1800 (kJ/s) .....	1065.4 / 1213.7
- Heat Rejection to Jacket Water @ ESP - Rpm 1500/1800 (kJ/s) .....	263 / 283
- Heat Rejection to Aftercooler @ ESP - Rpm 1500/1800 (kJ/s) .....	147 / 199
- Radiated Heat to Ambient @ ESP - Rpm 1500/1800 (kJ/s) .....	86.4 / 94.7
- Heat Rejected to Exhaust @ ESP - Rpm 1500/1800 (kJ/s) .....	569 / 637

## Exhaust system

Max. exhaust back pressure (mBar) .....	75
Max. exhaust temperature before turbocharger (°C) .....	730
Max. exhaust temperature after turbocharger (°C) .....	550
Exhaust flow @ PRP (m³/min) - Rpm 1500 / 1800 .....	148.2 / 167.9
Exhaust flow @ ESP (m³/min) - Rpm 1500 / 1800 .....	163.1 / 184.7
Min. diameter of exhaust pipe (mm) .....	200
Max. bending moment of exhaust gas exit flange (Nm) .....	10

	Model : <b>6M33G6D0/S</b>	Date : 22/03/23
	<b>PowerKit Switchable Engine Datasheet</b>	Page : 3 / 4

## Cooling system with standard radiator version 2020

System designed for ambient temperature up to (°C) <sup>1</sup>	50
Radiator type	Mechanical
Fan type	Belt driven pusher
Min. inside diameter of coolant outlet pipe (mm)	84
Coolant capacity of radiator and pipes (L)	115
Coolant alarm (shutdown) temperature (°C)	108
Thermostat opening temperature / full open temperature (°C)	80/92
Max. additional restriction for external cooling circuit (Bar)	
Coolant capacity of the engine (L)	44
Cooling fan airflow (m <sup>3</sup> /min)* - Rpm 1500 / 1800	783.3 / 1001
Fan absorbed power (kW) - Rpm 1500 / 1800	23.1 / 26.8
Additional restriction (for reference) - Duct allowance (Pa)	100

\* Air flow figure assumes the presence of the standard radiator provided, taking into consideration the backpressure caused

## Fuel system

Governor	ECU
Governor steady state speed stability at constant load (ISO 8528-5 Class G3) <sup>2</sup>	≤ +/- 0.5 %
Max. restriction at fuel inlet (Bar)	0.5
Max. pressure at fuel inlet (Bar)	
Max. fuel return restriction (Bar)	0.5
Max. fuel inlet temperature (°C)	50
Fuel supply flow (L/hr) - Rpm 1500 / 1800	900 / 950
Min. internal diameter of inlet pipe (mm)	14
Min. internal diameter of return pipe (mm)	14


## Electrical system

Electrical system voltage (negative to ground) (Vdc)	24
Starter power (kW)	8.5
Battery charger current (A)	55
Battery charger absorbed power (kW)	0.02
Max. electric resistance of starting circuit (Ω)	0.008
Min. sectional area of wire (mm <sup>2</sup> )	70
Min. cold start temperature without auxiliary starting device (°C) <sup>3</sup>	-5
Min. cold start temperature with auxiliary starting device (°C) <sup>3</sup>	-10

<sup>1</sup> The indicated value is based on an AOT value of 50°C for an engine tested at 100% of the ESP Power, reflecting temperature in an open condition, without an enclosure or container, without any airflow obstruction in the front of the radiator, without air recirculation, with free exhaust gas exit and with the engine thermostatic valve in its full open condition, without a closing plate present. The reference air restriction is equal to 50Pa. For the equivalent ATB (Air-to-Boil) performance in a customer or project basis, please consult Baudouin Application Engineering.

<sup>2</sup> This refers only to the frequency response of the engine and should not be confused with the performance class of the Generator Set, which is subject to additional contributing factors such as alternator selection and control settings.

<sup>3</sup> Engines used in emergency standby application or applications that require immediate start under load, they must be equipped with coolant heaters. Baudouin recommend heaters installation to be executed by providing constant coolant circulation across all the engine components. Two heaters are required for V-type engines, one per each side.

	Model : <b>6M33G6D0/S</b>	Date : 22/03/23
	<b>PowerKit Switchable Engine Datasheet</b>	Page : 4 / 4

Noise Rpm	1500	1800
Diesel engine noise (Acoustic power level) (dB(A)) .....	121.1	122
Noise - upper side (dB(A)) .....	104.3	105.2
Noise - right side (view from flywheel) (dB(A)) .....	104.1	105.2
Noise - left side (view from flywheel) (dB(A)) .....	106.7	107
Noise – front (radiator) side (dB(A)) .....	102.7	104.8
Noise – rear (flywheel) side (dB(A)) .....	104.3	105

Notes :

- Noise test made at 100% of the ESP power, at 1 mt. distance, on engine without radiator, without cooling fan and without silencer.
- Noise test refers to ISO 6798 norm : "Reciprocating internal combustion engines. Measurement of emitted airborne noise. Engineering method and survey method".

### Fuel consumption

Rating	1500 Rpm		1800 Rpm	
	gr/kWh	L/hr	gr/kWh	L/hr
100% ESP	202.5	174.8	216.4	189.9
100% PRP	198.5	159.5	203.4	162.2
75% PRP	190.4	114.8	194	116.1
50% PRP	192.6	77.4	199.8	79.7
25% PRP	213	42.8	227.3	45.3
Fuel consumption tolerance +/- 5%				

### Ratings definitions

#### Emergency Standby Power (ESP)

Emergency Standby Power is the maximum power available for a varying load for the duration of a main power network failure. The average load factor over 24 hours of operation should not exceed 70% of the engine's ESP power rating. Typical operational hours of the engine is 200 hours per year, with a maximum usage of 500 hours per year. This includes an annual maximum of 25 hours per year at the ESP power rating. No overload capability is allowed. The engine is not to be used for sustained utility paralleling applications.

#### Prime Power (PRP)

Prime Power is the maximum power available for unlimited hours of usage in a variable load application. The average load factor should not exceed 70% of the engine's PRP power rating during any 24 hour period. An overload capability of 10% is available, however, this is limited to 1 hour within every 12 hour period.

- All ratings are based on operating conditions under ISO 8528-1, ISO 3046, DIN6271. Performance tolerance of  $\pm 5\%$ .
- Test conditions : 100 kPa, 25°C air inlet temperature, relative humidity of 30%, with fuel density 0.84 kg/L. Derating may be required for conditions outside these; please contact the factory for details.
- Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan and optional equipment.